

DGTQF

"DGTQF": MICROCONTROLLER FOR INDUSTRIAL DOSAGE SYSTEMS



High performing microcontroller which, through the simple programming of the parameters, offers the possibility to manage single product dosage systems in loading or in unloading, or multiproduct dosages and mixtures. CE-M approvable (OIML R-76 / EN 45501).



The best solution
for advanced industrial
applications

MAIN FEATURES

- Easy to use 5-key waterproof keyboard.
- Highly efficient red LED display with 6 13-mm digits and 6 LEDs for showing active functions.
- Case for panel mounting in Abs according to DIN standard, 96x96x80mm (lxhxp). Perforation 90x88 mm (lxh) for panel mounting.
- A/D 24-bit sigma-delta conversion with 4 channels, up to 400 conv./sec. autoselect.
- Management of a weighing system from 1 to 4 channels (cells) with digital equalization.
- Connectable with up to 8 analogue load cells with 350 Ohm input resistance.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Up to 10.000e or multirange 2 x 3000e @ 0,3 $\mu\text{V/e}$ in CE-M approved version for legal for trade use.
- Calibration, Set-Up parameters, configurable from keyboard or PC with Dinitools.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- Time Date.
- Memory back-up for recording dosage data in case it's accidentally turned off.
- Printing the dosage and consumption data.
- From 12 Vdc to 24 Vdc power supply.

MAIN CERTIFICATIONS




- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R61 - MID
- OIML R51

I/O SECTION

- RS232/C bidirectional port configurable for connection with external units.
- RS485 bidirectional port configurable for network connection.
- Six 150 mA 48 Vac / 150 mA 60 Vdc (NO) photomofet outputs configurables according to the selected dosage function.
- 2 configurable optoisolator photocoupler inputs: 12÷24 Vdc, 5 mA min - 20 mA max for START/STOP dosage.
- Analogue 16 bit output (only for DGTQFAN model), configurable as 4-20mA, 0-5Vdc or 0-10Vdc. Maximum load applicable on the output current: 300Ohm. Minimum load applicable on the output voltage: 1kOhm.

DOSAGE CONFIGURATION

- Available dosage functions:

	<p><u>Single product dosage in loading functioning</u></p>
	<p><u>Single product dosage in unloading functioning</u></p>
	<p><u>Multi-product dosage functioning</u></p>



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

**DINI ARGEO
FRANCE sarl**
France

**DINI ARGEO
GMBH**
Germany

**DINI ARGEO
UK Ltd**
United Kingdom

**DINI ARGEO WEIGHING
INSTRUMENTS Ltd**
China

**DINI ARGEO
OCEANIA**
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE