

# 3590EGT-IECEX3GD

3590EGT-IECEX3GD "TOUCH" : TOUCH SCREEN INDICATOR FOR Ex 2 & 22 ZONES



Weight indicator with a big touch screen display, for ATEX 2 & 22 hazardous zones.

ATEX/IECEX marking:

II 3G Ex nR IIC T6 Gc X (0°C ≤ Ta ≤ 50°C) for gases

II 3D Ex tc IIIC T85°C Dc IP65 X (0°C ≤ Ta ≤ 50°C) for dust.

ATEX/IECEX marking with intrinsically safe connection for load cells:

II 3G Ex nR [ia] IIC T6 Gc X (0°C ≤ Ta ≤ 50°C) for gases.

II 3D Ex tc [ia] IIIC T85°C Dc IP65 X (0°C ≤ Ta ≤ 50°C) for dust.

Suitable for advanced industrial applications, it's fitted with 3 serial ports, Ethernet communication port, configurable printouts and integrated alibi memory.

CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:

**RICE LAKE WEIGHING SYSTEMS (AUSTRALIA)**

PACIFIC HIGHWAY 9/635 - NSW 2071 - KILLARA - AUSTRALIA  
Tel. +61 45 144 1755 Fax. 715-234-6967

**The best solution  
for advanced industrial  
applications**

## WHAT'S NEW

- IECEx certification.
- New enclosure with screwless front closure for easy cleaning of the indicator.
- PG7 and PG9 cable glands with adapters for 4 to 7 mm and 7 to 10 mm cable routing. Equipped with anti-friction system that does not require additional external cable fixing, as required by the IECEx scheme and ATEX directives.
- Available in specific version for direct connection to load cells installed in zone 1/21 and 0/20.

## TECHNICAL FEATURES

- **5,7' colour touch screen display.**
- **Multilanguage software.**
- 15-key alphanumerical waterproof keyboard.
- 3-way control light.
- Selectable QWERTY, AZERTY or QWERTZ keyboard integrated in the touch screen.
- **Stainless steel waterproof** enclosure, with new **IP68** protection system.
- Dimensions: 280x143x185mm.
- Suitable for use on the table, column or wall.
- Real time clock and permanent data storage.
- Alibi memory as standard, integrated on the motherboard.
- Slot for built-in micro SD to record the configuration, logos, and customized screens (upon request).
- **Functions available with DINITOOLS utility**
  - Configuration, data entry and print formatting.
  - Recording and filing of all the information on PC.
  - Complete retrieval of the configuration.
  - Instrument calibration with numeric values.
  - Customization of the screens.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. with automatic frequency selection and up to 8 signal linearisation points.
- 4 independent analogue channels for weight reading (up to 2 in E-AF03 version).
- Connection with up to 16 analogue load cells of 350 Ohm (45 load cells of 1000 Ohm).
- Up to 10.000e OIML or multi-range 3 x 3000e @ 0,3  $\mu$ V/d CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- Connectable to printers and labellers with free programming of the printout formats.
- Power supply from 110-240Vac line or 12-24 Vdc Max. 25.2W

## COMPLETE PROGRAMMABILITY FOR CUSTOMISED APPLICATIONS

- Thanks to the integrated development area, fully customised applications can be created independently:
  - Specific weighing softwares according to customer requirements
  - Tailor-made weighing softwares to replace terminals in existing installations
  - Wizards, messaging for the operator
  - Serial port management, protocol customization
  - Complete digital I/O management
  - Sequential or simultaneous automations
  - Data entry, tailor-made archives

Dini Argeo also offers the service of software development (to be quoted).

## STANDARD APPLICATIONS

- AF01: Totalization and formula weighing (standard)
- AF02: Piece/quantity counting (optional)
- AF03: Weighbridges - Vehicle In/Out (optional)
- AF04: Statistical check of prepackaged goods (optional)
- AF05: Price computing and industrial labelling (optional)
- AF08: Static wheel and axle weighing with 2 or more pads (optional)
- AF09: Software for dynamic or static axle weighing with 1 or 2 pads (optional)
- BATCH1: Single product dosage systems in loading and unloading (optional)
- BATCH: Software for multicomponent dosage systems in loading and unloading (optional, requires IOEXPB expansion board)

## I/O SECTION

- **1 Internal serial ETHERNET port, for connection to the company computer system** (excludes a serial port).
- 2 RS232 serial ports on terminals, for connection to printer, PC, radio module and optional interfaces.
- 1 RS485/RS232 serial port on terminals, for connection to weight repeater, remote scale, badge readers or digital load cells.
- 4 serial optoisolated outputs, up to 16 with optional board.
- 2 serial optoisolated inputs, up to 8 with optional board.
- External Profibus interface (optional), for automation management.
- Modbus RTU interface.
- Optional Bluetooth connection, for fast wireless programming of archives, via PC, tablet or smartphone.
- Analog output DAC16O requires IOEXPB expansion board.

## CUSTOMIZABLE DISPLAYS

- Thanks to the programmable Touch Screen display, it is possible to create the interface tailored to each application:



- The PC software "**Dini Display Tool**" allows for the quick customisation of the TOUCH display.





[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena - Italy  
Tel. +39.0536 843418

***RICE LAKE WEIGHING SYSTEMS (AUSTRALIA)***

*PACIFIC HIGHWAY 9/635 - NSW 2071 - KILLARA - AUSTRALIA*

*Tel. +61 45 144 1755 Fax. 715-234-6967*

***SALES AND TECHNICAL ASSISTANCE SERVICE***